

# SAFETY DATA SHEET

## Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols 1813

**Product number**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Lacquer

#### 1.3. Details of the supplier of the safety data sheet

**Supplier**

Sole Juice Ltd. Unit 15 Aspen Court, Centurion  
Business Park, Bessemer Way, Rotherham,  
United Kingdom, S60 1FB.  
www.subliglaze.com  
+44 (0)1709 296 366  
+44 (0)1709 718 661  
info@SoleJuice.com

#### 1.4. Emergency telephone number

**Emergency telephone** (+44)1709 296 366 (Hours 09:00 - 17:00 Mon to Fri)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

**Physical hazards** Aerosol 1 - H222, H229

**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336

**Environmental hazards** Not Classified

**Classification (67/548/EEC or 1999/45/EC)** F+; R12. Xi; R36. R66, R67

**Human health** Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

**Environmental** The product is not expected to be hazardous to the environment.

**Physicochemical** Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

#### 2.2. Label elements

**Pictogram**



**Signal word** Danger

**Hazard statements**  
H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

<b>Precautionary statements</b>	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a POISON CENTER/ doctor if you feel unwell.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p>
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Contains</b>	ACETONE, N-BUTYL ACETATE, HYDROCARBONS, C9, AROMATICS
<b>Supplementary precautionary statements</b>	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>DIMETHYL ETHER</b>		<b>30-60%</b>
CAS number: 115-10-6	EC number: 204-065-8	
<b>Classification</b>		
Flam. Gas 1 - H220		
Press. Gas, Liquefied - H280		
<b>ACETONE</b>		<b>30-60%</b>
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX
<b>Classification</b>		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

<b>N-BUTYL ACETATE</b>		<b>1-5%</b>
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-XXXX
<b>Classification</b>		
Flam. Liq. 3 - H226 STOT SE 3 - H336		
<b>2-BUTOXYETHANOL</b>		<b>1-5%</b>
CAS number: 111-76-2	EC number: 203-905-0	REACH registration number: 01-2119475108-36-XXXX
<b>Classification</b>		
Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319		
<b>HYDROCARBONS, C9, AROMATICS</b>		<b>1-5%</b>
CAS number: 64742-95-6	EC number: 918-668-5	REACH registration number: 01-2119455851-35-XXXX
<b>Classification</b>		
Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
<b>Skin contact</b>	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards.
----------------------------	--

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor**                      Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media**    Foam, carbon dioxide or dry powder.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards**                      Containers can burst violently or explode when heated, due to excessive pressure build-up.

#### 5.3. Advice for firefighters

**Protective actions during firefighting**                      Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions**                      Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

#### 6.2. Environmental precautions

**Environmental precautions**                      Avoid discharge into drains.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up**                      Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

#### 6.4. Reference to other sections

**Reference to other sections**                      For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions**                      Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

**Advice on general occupational hygiene**                      Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions**                      Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

#### 7.3. Specific end use(s)

**Specific end use(s)**                      The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limits

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

### DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): 400 ppm

Short-term exposure limit (15-minute): 500 ppm

### ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

### N-BUTYL ACETATE

Short-term exposure limit (15-minute): WEL 966 mg/m<sup>3</sup> 200 ppm

Long-term exposure limit (8-hour TWA): WEL 724 mg/m<sup>3</sup> 150 ppm

### 2-BUTOXYETHANOL

Short-term exposure limit (15-minute): WEL 246 mg/m<sup>3</sup> 50 ppm

Long-term exposure limit (8-hour TWA): WEL 123 mg/m<sup>3</sup> 25 ppm

WEL = Workplace Exposure Limit

### DIMETHYL ETHER (CAS: 115-10-6)

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 1894 mg/m <sup>3</sup> Consumer - Inhalation; Long term systemic effects: 471 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 0.155 mg/l - Marine water; 0.016 mg/l - Intermittent release; 1.549 mg/l - Sediment (Freshwater); 0.681 mg/kg - Sediment (Marinewater); 0.069 mg/kg - STP; 160 mg/l - Soil; 0.045 mg/kg

### ACETONE (CAS: 67-64-1)

<b>DNEL</b>	Workers - Dermal; Long term systemic effects: 186 mg/kg/day Workers - Inhalation; Short term local effects: 2420 mg/m <sup>3</sup> Workers - Inhalation; Long term systemic effects: 1210 mg/m <sup>3</sup>
<b>PNEC</b>	- Sediment (Freshwater); 30.4 mg/kg - Sediment (Marinewater); 3.04 mg/kg - Marine water; 1.06 mg/l - Soil; 29.5 mg/kg

### N-BUTYL ACETATE (CAS: 123-86-4)

<b>DNEL</b>	Consumer - Inhalation; Short term local effects: 859.7 mg/m <sup>3</sup> Consumer - Inhalation; Short term systemic effects: 859.7 mg/m <sup>3</sup> Workers - Inhalation; Short term systemic effects: 960 mg/m <sup>3</sup> Workers - Inhalation; Short term local effects: 960 mg/m <sup>3</sup> Consumer - Inhalation; Long term local effects: 102.34 mg/m <sup>3</sup> Workers - Inhalation; Long term local effects: 480 mg/m <sup>3</sup> Consumer - Inhalation; Long term systemic effects: 102.34 mg/m <sup>3</sup> Workers - Inhalation; Long term systemic effects: 480 mg/m <sup>3</sup>
-------------	--

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

<b>PNEC</b>	- Fresh water; 0.18 mg/l
	- Sediment (Freshwater); 0.981 mg/kg
	- Sediment (Marinewater); 0.981 mg/kg
	- Marine water; 0.018 mg/l
	- STP; 35.6 mg/l
	- Soil; 0.0903 mg/kg

### 2-BUTOXYETHANOL (CAS: 111-76-2)

<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 3.2 mg/kg/day
	Consumer - Dermal; Short term systemic effects: 44.5 mg/kg/day
	Workers - Dermal; Short term systemic effects: 89 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 38 mg/kg/day
	Workers - Dermal; Long term systemic effects: 75 mg/kg/day
	Consumer - Inhalation; Short term local effects: 123 mg/m <sup>3</sup>
	Consumer - Inhalation; Short term systemic effects: 426 mg/m <sup>3</sup>
	Workers - Inhalation; Short term systemic effects: 246 mg/m <sup>3</sup>
	Consumer - Inhalation; Long term systemic effects: 49 mg/m <sup>3</sup>
Workers - Inhalation; Long term systemic effects: 98 mg/m <sup>3</sup>	

<b>PNEC</b>	- Fresh water; 8.8 mg/l
	- Sediment (Freshwater); 34.6 mg/kg
	- Sediment (Marinewater); 3.46 mg/kg
	- Marine water; 0.88 mg/l
	- STP; 463 mg/l
	- Soil; 2.8 mg/kg

## 8.2. Exposure controls

<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
<b>Hand protection</b>	No specific requirements are anticipated under normal conditions of use.
<b>Other skin and body protection</b>	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
<b>Respiratory protection</b>	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

## **SECTION 9: Physical and Chemical Properties**

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Clear.
<b>Odour</b>	Solvents
<b>Odour threshold</b>	No information available.
<b>pH</b>	No information available.
<b>Melting point</b>	No information available.
<b>Initial boiling point and range</b>	-25 (-25 TO 215)°C @
<b>Flash point</b>	-41°C CC (Closed cup).
<b>Evaporation rate</b>	No information available.
<b>Evaporation factor</b>	No information available.

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

<b>Flammability (solid, gas)</b>	No information available.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 0.6 % Upper flammable/explosive limit: 32 %
<b>Vapour pressure</b>	No information available.
<b>Vapour density</b>	No information available.
<b>Relative density</b>	0.768
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	No information available.
<b>Auto-ignition temperature</b>	22°C
<b>Decomposition Temperature</b>	No information available.
<b>Viscosity</b>	No information available.
<b>Explosive properties</b>	No information available.
<b>Oxidising properties</b>	No information available.

### 9.2. Other information

**Other information** None.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** No test data specifically related to reactivity available for this product or its ingredients.

### 10.2. Chemical stability

**Stability** The product may not be stable under some conditions of storage or use.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None known.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

### 10.5. Incompatible materials

**Materials to avoid** None known.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** None at ambient temperatures.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**ATE oral (mg/kg)** 85,808.58

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 72,607.26

#### Acute toxicity - inhalation

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

ATE inhalation (vapours mg/l) 726.07

<b>Inhalation</b>	May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.
<b>Skin contact</b>	Skin irritation should not occur when used as recommended.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Acute and chronic health hazards</b>	No known chronic or acute health risks.
<b>Route of entry</b>	Inhalation Skin and/or eye contact

### DIMETHYL ETHER

#### Acute toxicity - inhalation

Acute toxicity inhalation (LC <sub>50</sub> gases ppmV)	164,000.0
Species	Rat
ATE inhalation (gases ppm)	164,000.0

### ACETONE

#### Acute toxicity - oral

Acute toxicity oral (LD <sub>50</sub> mg/kg)	5,800.0
Species	Rat
ATE oral (mg/kg)	5,800.0

#### Acute toxicity - dermal

Acute toxicity dermal (LD <sub>50</sub> mg/kg)	7,800.0
Species	Rabbit
ATE dermal (mg/kg)	7,800.0

#### Acute toxicity - inhalation

Acute toxicity inhalation (LC <sub>50</sub> vapours mg/l)	21.0
Species	Rat
ATE inhalation (vapours mg/l)	21.0

### N-BUTYL ACETATE

#### Acute toxicity - oral

Acute toxicity oral (LD <sub>50</sub> mg/kg)	10,760.0
Species	Rat



## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

ATE oral (mg/kg) 10,760.0

### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 14,113.0

Species Rabbit

ATE dermal (mg/kg) 14,113.0

### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 23.4

Species Rat

ATE inhalation (vapours mg/l) 23.4

## 2-BUTOXYETHANOL

### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 1,300.0

Species Rat

ATE oral (mg/kg) 1,300.0

### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,001.0

Species Guinea pig

ATE dermal (mg/kg) 1,100.0

### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 11.0

Species Rat

ATE inhalation (vapours mg/l) 11.0

## SECTION 12: Ecological Information

### 12.1. Toxicity

#### DIMETHYL ETHER

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 4001 mg/l, *Poecilia reticulata* (Guppy)

Acute toxicity - aquatic invertebrates EC<sub>50</sub>, 48 hours: 4001 mg/l, *Daphnia magna*

Acute toxicity - aquatic plants EC<sub>50</sub>, 96 hours: 154.9 mg/l, Fish

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

### ACETONE

**Acute toxicity - fish** EC<sub>50</sub>, 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, : 8800 mg/l, Daphnia magna

### N-BUTYL ACETATE

**Acute toxicity - fish** LC<sub>50</sub>, 24 hours: 54 mg/l, Algae  
LC<sub>50</sub>, 96 hours: 18 mg/l, Pimephales promelas (Fat-head Minnow)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 44 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: 647.7 mg/l, Scenedesmus subspicatus

### 2-BUTOXYETHANOL

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 1474 mg/l, Onchorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 1550 mg/l, Daphnia magna

#### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

#### 12.3. Bioaccumulative potential

**Partition coefficient** No information available.

#### 12.4. Mobility in soil

**Mobility** No data available

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**General information** Dispose of waste product or used containers in accordance with local regulations

**Disposal methods** Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

### **SECTION 14: Transport information**

#### 14.1. UN number

**UN No. (ADR/RID)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

UN No. (ADN) 1950

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS, FLAMMABLE

Proper shipping name (IMDG) AEROSOLS, FLAMMABLE

Proper shipping name (ICAO) AEROSOLS, FLAMMABLE

Proper shipping name (ADN) AEROSOLS, FLAMMABLE

### 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

### Transport labels



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

## Sole Juice Limited - Subli Glaze UV Protection Coating DC-UV400 400ml Aerosols

**EU legislation**

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Revision date</b>	20/01/2017
<b>Revision</b>	2
<b>Supersedes date</b>	21/08/2014
<b>SDS number</b>	4933
<b>Hazard statements in full</b>	<p>H220 Extremely flammable gas.  H222 Extremely flammable aerosol.  H222 Extremely flammable aerosol.  H225 Highly flammable liquid and vapour.  H225 Highly flammable liquid and vapour.  H226 Flammable liquid and vapour.  H226 Flammable liquid and vapour.  H229 Pressurised container: may burst if heated  H229 Pressurised container: may burst if heated  H280 Contains gas under pressure; may explode if heated.  H302 Harmful if swallowed.  H304 May be fatal if swallowed and enters airways.  H304 May be fatal if swallowed and enters airways.  H312 Harmful in contact with skin.  H315 Causes skin irritation.  H319 Causes serious eye irritation.  H319 Causes serious eye irritation.  H332 Harmful if inhaled.  H335 May cause respiratory irritation.  H336 May cause drowsiness or dizziness.  H336 May cause drowsiness or dizziness.  H411 Toxic to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.